

## Specification

Item	Model	LA-600
<b>Output @8Ω/1KHz</b>		<b>300W</b>
<b>Output @4Ω/1KHz</b>		<b>500W</b>
<b>Frequency Response</b>		<b>20Hz-250Hz (上限截止频率可调)</b>
<b>THD%</b> <b>(10% RMS, 1KHz)</b>		<b>&lt;0.5%</b>
Conversion Rate (RMS POWER, 1KHz)		<b>&gt;20V/μs</b>
<b>Damping Factor (RMS, 1KHz)</b>		<b>&gt;200</b>
Dynamic Range		<b>≥95dB</b>
<b>SNR</b>		<b>≥95dB</b>
<b>Sensitivity (RMS, 1KHz)</b>		<b>1 。 28V rms</b>
<b>Voltage Gain</b>		<b>36dB</b>
<b>Input Impedance</b>		<b>20K balanced / 10K unbalanced</b>
<b>N/W</b>		<b>1.7Kg</b>
Average Power Dissipation		<b>200W</b>
circuit type		<b>CLASS D</b>
<b>Protection</b>		DC protection, soft start protection, Thermal Protection, Short circuit protection, Peak pressure limit
<b>Voltage/Frequency</b>	<b>AC100V--240V/50Hz~60Hz(accept custom service)</b>	

注：以上的测试数据都是在标准的电压 220V/50Hz，标准的正弦波电网波形下得到的数据